



1 - IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Preparation:

Name: DURCISSEUR FRS

Product code: 21040000 D.

Company/business:

Registered company name: MAP YACHTING.

Address : ZI ATHELIA IV – 296 Av de la Tramontane – 13705 LA CIOTAT - France.

Telephone : 33 (0)4 42 98 14 50 Fax :33 (0)4 42 98 14 51. Email : sales@map-yachting.com

Emergency telephone No.: 33 (0)1 45 42 59 59 .

Association/Organisation: ORFILA.

2 - COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous substances present on their own.

(present in the preparation at a sufficient concentration to give it the toxicological characteristics it would have in a 100% pure state)

INDEX 601-022-00-9 CAS 1330-20-7 CE 215-535-7 O-XYLENE | Concentration $\geq 10.00\%$ and $< 25.00\%$. Symbol: Xn R: 10-38-20/21

Other substances representing a hazard:

INDEX 601-023-00-4 CAS 100-41-4 CE 202-849-4 ETHYLBENZENE | Concentration $\geq 2.50\%$ and $< 10.00\%$. Symbol: Xn F R: 11-20

INDEX 615-011-00-1 CAS 822-06-0 CE 212-485-8 HEXAMETHYLENE-DI-ISOCYANATE | Concentration $\geq 0.00\%$ and $< 2.50\%$. Symbol: T R: 23-36/37/38-42/43

Substances present at a concentration below the minimum danger threshold.

INDEX 607-195-00-7 CAS 108-65-6 CE 203-603-9 2-METHOXY-1-METHYLETHYL ACETATE | Concentration $\geq 10.00\%$ and $< 25.00\%$. Symbol: Xi R: 10-36

Other substances with occupational exposure limits.

No known substance in this category present.

3 - IDENTIFICATION OF HAZARDS

This product is classed: Flammable.

The preparation causes sensitisation of the skin and respiratory organs. It also irritates the skin and prolonged contact may aggravate this effect.

Possibility of noxious effects with symptoms of slight poisoning by inhalation and contact with the skin.

4 - FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing in an unconscious person.

In the event of exposure by inhalation.

If a large quantity is inhaled, move the patient into the fresh air and keep him/her warm and still.

If breathing is irregular or has stopped, effect mouth-to-mouth resuscitation and call a doctor.

Do not give the patient anything orally.

In the event of splashes or contact with eyes.

Wash thoroughly with soft, clean water for 15 minutes holding the eyelids open.

Refer the patient to an ophthalmologist, in particular if there is any redness, pain or visual impairment.

In the event of splashes or contact with skin.

Remove contaminated clothing and wash the skin thoroughly with soap and water or a recognised cleaner.

DO NOT use solvents or thinners.

If the contaminated area is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital

In the event of swallowing.

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.

Keep still. DO NOT induce vomiting.



If swallowed accidentally, call a doctor to assess the need for monitoring and subsequent treatment in hospital. Show him the label.

5 - FIRE-FIGHTING MEASURES

Chemical powders, carbon dioxide and other extinguishing gas are suitable for small fires.

In the event of fire, the recommended extinguishing agents are:

Carbon dioxide, chemical powders, foams, and other extinguishing gases.

In the event of fire, use specifically suitable extinguishing agents. Never use water.

Extinguishing agents not to be used

Water is not generally recommended since it can be ineffective; however, it can be used successfully to cool containers exposed to the fire and to disperse fumes.

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

Prevent the effluent of fire-fighting measures from entering drains or waterways.

Special equipment for fire-fighting personnel.

Fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.

6 - ACCIDENTAL RELEASE MEASURES

Safety precautions:

Eliminate any possible source of ignition and ventilate the premises.

On account of the organic solvents contained in the preparation, eliminate sources of ignition and ventilate the premises.

Avoid inhaling the vapors.

Avoid any contact with the skin and eyes.

Consult the safety measures listed under headings 7 and 8.

Environmental safety precautions:

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatom earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

Use drums to dispose of waste recovered in accordance with applicable regulations (see heading 13).

If the product contaminates waterways, rivers or drains, alert the relevant authorities in accordance with statutory procedures

Cleaning methods:

Clean preferably with a detergent, do not use solvents.

Contaminated areas must be cleaned very quickly.

A possible decontaminant for flammable products may be: (expressed by volume) water (45 parts), ethanol or isopropanol (50 parts), concentrated ammonia (d-0.880) (5 parts). For non-flammable products: sodium carbonate (5 parts), water (95 parts).

These residues must be stored for disposal in accordance with applicable regulations (see 13).

7 - HANDLING AND STORAGE

The regulations relating to storage premises apply to workshops where the product is handled.

Anyone with a history of asthma, allergies, chronic or periodic respiratory problems must on no account use these preparations

Anyone with a history of skin sensitisation must on no account handle such products

Handling:

Handle in well-ventilated areas.

The vapors are denser than air. They can spread along the ground and form explosive mixtures with air

Prevent the formation of flammable or explosive concentrations in air and avoid vapor concentrations higher than the occupational exposure limits.

Fire prevention:

Prevent the accumulation of electrostatic charges with connections to earth

The preparation may become electrostatically charged; always place on the ground during transfer. Wear antistatic shoes and clothes and make floors of conductive materials.

Use the product in premises where there are no naked flames or other sources of ignition and have protected electrical equipment

Keep packages tightly closed and away from sources of heat, sparks and naked flames.

Do not use tools which may produce sparks. Do not smoke.

Prevent access by unauthorised personnel.



Recommended equipment and procedures

For personal safety, see §8.
 Observe precautions stated on label and also industrial safety regulations
 Avoid inhaling solvent vapors and spray-gun aerosols
 Packages which have been opened must be reclosed carefully and stored in an upright position
 Avoid inhaling vapors.
 Where the personnel must carry out work in a booth, whether for spraying or otherwise, the ventilation may be inadequate to control particles and solvent vapors in every case.
 It is therefore recommended that personnel wear masks with a compressed air supply during spraying operations until the concentration of particles and solvent vapors has fallen below the exposure limits.
 Avoid contact of product with the skin and eyes

Prohibited equipment and procedures.

Smoking, eating and drinking are prohibited in premises where the preparation is used
 Never open the packages under pressure

Storage.

Keep the container tightly closed in a dry, well-ventilated place
 Keep away from all sources of ignition - do not smoke.
 Keep well away from all sources of ignition, heat and direct sunlight
 The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area.

8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

Anyone with a history of skin sensitisation, asthma, allergies, chronic or periodic respiratory problems must on no account use these preparations

Technical measures.

Ensure adequate ventilation, if possible with extractor fans at work posts and appropriate general extraction.
 If this ventilation is insufficient to maintain the concentration of solvent vapors below the exposure limits, wear breathing apparatus

Exposure limits per INRS ND 2098-174-99 and ND 2114-176-99:

France	VME-ppm:	VME-mg/m3:	VLE-ppm:	VLE-mg/m3:	Notes:	TMP N°:
822-06-0	0,01	0,075	0,02	0,15	AR	62
108-65-6	-	-	-	-	-	-
100-41-4	100	435	-	-	-	84
1330-20-7	100	435	150	650	-	4bis, 84
Germany	Class:	MAK-ppm:	MAK-mg/m3:	Notes:	Notes:	
822-06-0	I	0,005	0,035	Sens		
108-65-6	I	50	270	C		
100-41-4	I	100	440	D,*		
1330-20-7	II,1	100	440	D,*		
ACGIH(TLV)	TWA-ppm:	TWA-mg/m3:	STEL-ppm:	STEL-mg/m3:	Notes:	Notes:
822-06-0	0,005	0,034	-	-	-	-
108-65-6	-	-	-	-	-	-
100-41-4	100	434	125	543	-	S
1330-20-7	100	434	150	651	A4	S

Exposure limits per 2000/39/EC and 98/24/EC:

EC	VME-ppm:	VME-mg/m3:	VLE-ppm:	VLE-mg/m3:	Notes:
108-65-6	50	275	100	550	Peau
100-41-4	100	442	200	884	Peau
1330-20-7	50	221	100	442	Peau

Other values (2003):

UK/MEL	TWA:	STEL:	Ceiling:	Definition:	Criterion:
822-06-0	0.02 mg/m3	0.07 mg/m3	-	-	-
UK/OES	TWA:	STEL:	Ceiling:	Definition:	Criterion:
108-65-6	50 ppm	100 ppm	-	-	-

100-41-4	100 ppm	125 ppm	-	-	-
1330-20-7	50 ppm	100 ppm	-	-	-
Germany/MAK	TWA:	STEL:	Ceiling:	Definition:	Criterion:
822-06-0	0.005 ppm	0.005 ppm	0.01	-	-
108-65-6	50 ppm	50 ppm	-	-	-
1330-20-7	100 ppm	200 ppm	-	-	-

Safety breathing apparatus:

With this preparation, avoid in particular any inhalation of vapors.

Hand protection.

Protective creams may be used for exposed skin, but they should not be applied after contact with the product.

Protective creams may be used for exposed skin, but they should not be applied after contact with the product.

Due to the solvents present, it is recommended that polyvinyl alcohol or nitrile rubber gloves be worn.

Eye and face protection.

Use eye protectors designed to protect against liquid splashes

Skin protection.

Wear antistatic clothing made of natural fibre or synthetic fibre resistant to high temperatures.

After contact with the product, any contaminated part of the body shall be washed

For further information, see § 11 of S.D.S. - Toxicological information.

9 - PHYSICAL AND CHEMICAL PROPERTIES

Density:	> 1
Acid/base character of preparation:	not relevant.
Solubility of preparation in water:	Insoluble.
Vapour tension at 50°C of volatile constituents:	Below 110 kPa (1.10 bar).
Physical state:	fluid liquid
Flash point interval:	23°C. < Flash point: ≤ 55°C.
The pH is impossible to measure or its value is not relevant.	
Self-ignition temperature:	500 °C.
Decomposition temperature:	not relevant.
Melting temperature interval:	-25 °C.
Average distillation temperature of solvents contained:	144 °C.

10 - STABILITY AND REACTIVITY

When exposed to high temperatures, the preparation may release dangerous decomposition products such as carbon monoxide and dioxide, smoke and nitrogen oxide

It may also release hydrogen cyanide, amines and alcohols.

Keep away from oxidising agents and strongly acidic or basic materials to avoid exothermic reactions

Exothermic reactions occur with amines and alcohols. The preparations react slowly with water and give off carbonic gas which may produce pressure increases in closed packages

11 - TOXICOLOGICAL INFORMATION

No data is available regarding the preparation itself.

Exposure to vapors from solvents contained in the preparation beyond the exposure limits stated may produce effects harmful to health, such as:

Irritation of mucous membrane and respiratory system, kidneys, liver and central nervous system.

Symptoms produced will include headaches, numbness, dizziness, fatigue, muscular asthenia and, in extreme cases, loss of consciousness.

Prolonged or repeated contact with the preparation may strip the skin of its natural oil and thus cause non-allergic dermatitis on contact and absorption through the epidermis.

Splashes in the eyes may cause irritation and reversible damage

It is generally agreed that substances contained are likely to cause, among certain predisposed subjects, a sensitisation reaction in the event of inhalation and exposure to the skin.

Based on the properties of isocyanates and taking into account toxicological data for similar preparations, this preparation may cause irritation and/or sensitisation of the respiratory system.

It may also lead to asthma, respiratory problems and angina

Those susceptible may display asthmatic symptoms when exposed to atmospheres with an isocyanate concentration well below those of the VLE: exposure limits.

Repeated exposure may cause permanent respiratory problems.

12 - ECOLOGICAL INFORMATION

No ecological data on the product itself is available.

The product must not be allowed to run into drains or waterways.

Other data:

Germany: WGK 2 (VwVwS vom 17/05/99, KBws)

13 - DISPOSAL CONSIDERATIONS

Do not pour into drains or waterways.

14 - TRANSPORT INFORMATION

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport
UN1263=PAINT RELATED MATERIAL (including paint thinning or reducing compound)

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.		
	3	F1	III	3	33	LQ7	163-640E		
IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.			
	3	-	III	5 L	F-E,S-E	163 223 944 955			
IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	
	3	-	III	309	60 L	310	220 L	A3, A72	
	3	-	III	Y309	10 L	-	-	-	

15 - STATUTORY INFORMATION

This preparation was classified in compliance with the directive known as <All preparations> 1999/45/EC and its adaptations

In addition directive 2001/59/EC with the 28° adaptation of directive 67/548/EC (Hazardous substances) have been taken into account.

Contains compounds with an isocyanate base - refer to the information supplied by the manufacturer. This information is found on this safety data sheet

Preparation classification.

Harmful. Flammable.

Contains:

601-022-00-9 O-XYLENE

601-023-00-4 ETHYLBENZENE

615-011-00-1 HEXAMETHYLENE-DI-ISOCYANATE

Particular hazards associated with the preparation and safety recommendations:

R 42/43	May cause sensitization by inhalation and skin contact.
R 20/21	Harmful by inhalation and in contact with skin.
R 10	Flammable.
	Contains isocyanates. See information supplied by the manufacturer.
S 23	Do not breathe gas/fumes/vapour/spray (appropriate wording to be specified by the manufacturer).
S 36/37	Wear suitable protective clothing and gloves.
S 45	In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
S 25	Avoid contact with eyes.
S 38	In case of insufficient ventilation, wear suitable respiratory equipment.
S 60	This material and its container must be disposed of as hazardous waste.
S 9	Keep container in a well-ventilated place.

Particular provisions:

Germany: WGK 2 (VwVwS vom 17/05/99, KBws)

16 - OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The product must not be used for any purposes other than those specified under heading 1 without first obtaining written handling instructions.



MATERIAL SAFETY DATA SHEETS



It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.
The information given on this safety data sheet must be regarded as a description of the safety requirements relating to our product and not a guarantee of its properties

—