

1 - IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Identification of the substance or preparation:

Name: **UNDERCOAT MPO 500**

Product code: BV ALU

Company/undertaking identification:

Registered company name: SICOMIN - PAINT SYSTEMS

Address: ZI ATHELIA IV – 296 Av de la Tramontane – 13705 LA CIOTAT - France

Telephone: 33 (0)4 42 98 14 50 Fax :33 (0)4 42 98 14 51. Email : paint@sicomin.com

Emergency telephone: 01 45 42 59 59.

Association/Organisation: ORFILA

2 - COMPOSITION/INFORMATION ON INGREDIENTS

Full text of risk phrases appearing in section 2: see section 16.

Hazardous substances present on their own:

(present in the preparation at a sufficient concentration to give it the toxicological characteristics it would have in a 100% pure state)

INDEX	CAS	EC	Name	Symb.	R:	%
030-011-00-6	7779-90-0	231-944-3	TRIZINC BIS(ORTHOPHOSPHATE)	N	50/53	25 <= x % < 50
601-022-00-9	1330-20-7	215-535-7	O-XYLENE	Xn	10 38 20/21	10 <= x % < 25

Other substances representing a hazard:

INDEX	CAS	EC	Name	Symb.	R:	%
601-024-00-X	98-82-8	202-704-5	CUMENE	Xn N	10 37 51/53 65	0 <= x % < 2.5
601-025-00-5	108-67-8	203-604-4	MESITYLENE	Xi N	10 37 51/53	0 <= x % < 2.5
601-043-00-3	95-63-6	202-436-9	1,2,4-TRIMETHYLBENZENE	Xn N	10 36/37/38 51/53 20	2.5 <= x % < 10

Substances present at a concentration below the minimum danger threshold:

No known substance in this category present.

Other substances with occupational exposure limits:

No known substance in this category present.

Other components

INDEX	CAS	EC	Name	Symb.	R:	%
649-330-00-2	64742-82-1	265-185-4	NAPHTHA (PETROLEUM), HYDRODESULFURIZED HEAVY	Xn	65	0 <= x % < 2.5
649-356-00-4	64742-95-6	265-199-0	SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM.	Xn	65	2.5 <= x % < 10

3 - IDENTIFICATION OF HAZARDS

This product is classed: Flammable.

Possibility of irritation to the skin.

On contact with water or moist air, the preparation releases dangerous quantities of highly inflammable gases at a minimum rate of 1 litre/kg/h

Possibility of noxious effects with symptoms of slight poisoning by inhalation and contact with the skin.

Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

4 - FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing in an unconscious person.

In the event of exposure by inhalation:

If a large quantity is inhaled, move the patient into the fresh air and keep him/her warm and still.

If breathing is irregular or has stopped, effect mouth-to-mouth resuscitation and call a doctor.

Do not give the patient anything orally.

In the event of splashes or contact with eyes:

Wash thoroughly with soft, clean water for 15 minutes holding the eyelids open.

Refer the patient to an ophthalmologist, in particular if there is any redness, pain or visual impairment.

In the event of splashes or contact with skin:

Remove contaminated clothing and wash the skin thoroughly with soap and water or a recognised cleaner.

DO NOT use solvents or thinners.

If the contaminated area is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital

In the event of swallowing:

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.



Keep still. DO NOT induce vomiting.
Call a doctor immediately and show him the label.

5 - FIRE-FIGHTING MEASURES

Chemical powders, carbon dioxide and other extinguishing gas are suitable for small fires.

Suitable extinguishing media:

Carbon dioxide, chemical powders, foams, and other extinguishing gases.

In the event of fire, use specifically suitable extinguishing agents. Never use water.

Extinguishing media which must not be used for safety reasons:

Water is not generally recommended since it can be ineffective; however, it can be used successfully to cool containers exposed to the fire and to disperse fumes.

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

Prevent the effluent of fire-fighting measures from entering drains or waterways.

Special protective equipment for fire-fighters:

Fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.

Due to the toxicity of the gas emitted on thermal decomposition of the products, fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.

6 - ACCIDENTAL RELEASE MEASURES

Personal precautions:

On account of the organic solvents contained in the preparation, eliminate sources of ignition and ventilate the premises.

Avoid inhaling the vapors.

Avoid any contact with the skin and eyes.

Consult the safety measures listed under headings 7 and 8.

Environmental precautions:

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

Use drums to dispose of waste recovered in accordance with applicable regulations (see heading 13).

If the product contaminates waterways, rivers or drains, alert the relevant authorities in accordance with statutory procedures

Methods for cleaning up:

Clean preferably with a detergent, do not use solvents.

7 - HANDLING AND STORAGE

The regulations relating to storage premises apply to workshops where the product is handled.

Handling:

Handle in well-ventilated areas.

The vapors are denser than air. They can spread along the ground and form explosive mixtures with air

Prevent the formation of flammable or explosive concentrations in air and avoid vapor concentrations higher than the occupational exposure limits.

Fire prevention:

Prevent the accumulation of electrostatic charges with connections to earth

The preparation may become electrostatically charged; always place on the ground during transfer. Wear antistatic shoes and clothes and make floors of conductive materials.

Use the product in premises where there are no naked flames or other sources of ignition and have protected electrical equipment

Keep packages tightly closed and away from sources of heat, sparks and naked flames.

Do not use tools which may produce sparks. Do not smoke.

Prevent access by unauthorised personnel.

Recommended equipment and procedures:

For personal safety, see §8.

Observe precautions stated on label and also industrial safety regulations

Packages which have been opened must be reclosed carefully and stored in an upright position

Avoid inhaling vapors.

Avoid contact of product with the skin and eyes

Prohibited equipment and procedures:

Smoking, eating and drinking are prohibited in premises where the preparation is used

Never open the packages under pressure

Never pour water into this product

Storage:

Keep the container tightly closed in a dry, well-ventilated place

Keep away from all sources of ignition - do not smoke.



Keep well away from all sources of ignition, heat and direct sunlight
 The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area.

8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

Use personal protection equipment as per Directive 89/686/EEC.

Technical measures:

Ensure adequate ventilation, if possible with extractor fans at work posts and appropriate general extraction.

If this ventilation is insufficient to maintain the concentration of solvent vapors below the exposure limits, wear breathing apparatus

Exposure limit values per INRS ND 2098-174-99 and ND 2114-176-99:

France	VME-ppm:	VME-mg/m3:	VLE-ppm:	VLE-mg/m3:	Notes:	TMP N°:
95-63-6	-	-	-	-	-	-
108-67-8	-	-	-	-	-	-
98-82-8	50	245	-	-	*	84
1330-20-7	100	435	150	650	-	4 Bis,84
Germany	Class:	MAK-ppm:	MAK-mg/m3:	Notes:	Notes:	
95-63-6	-	-	-	-	-	-
108-67-8	-	-	-	-	-	-
98-82-8	II,2	50	250	C,*	-	-
1330-20-7	II,1	100	440	D,*	-	-
ACGIH(TLV)	TWA-ppm:	TWA-mg/m3:	STEL-ppm:	STEL-mg/m3:	Notes:	Notes :
95-63-6	-	-	-	-	-	-
108-67-8	-	-	-	-	-	-
98-82-8	50	246	-	-	(*)	-
1330-20-7	100	434	150	651	A4	S

Exposure limit values per 2000/39/EC and 98/24/EC:

CE	VME-ppm:	VME-mg/m3:	VLE-ppm:	VLE-mg/m3:	Notes:
95-63-6	20	100	-	-	-
108-67-8	20	100	-	-	-
98-82-8	20	100	50	250	peau
1330-20-7	50	221	100	442	peau

Exposure limit values (2003):

UK/OES	TWA:	STEL:	Ceiling:	Definition:	Criterion:
95-63-6	25 ppm	-	-	-	-
108-67-8	25 ppm	-	-	-	-
98-82-8	25 ppm	50 ppm	-	-	-
1330-20-7	50 ppm	100 ppm	-	-	-

Respiratory protection:

With this preparation, avoid in particular any inhalation of vapors.

Hand protection:

Protective creams may be used for exposed skin, but they should not be applied after contact with the product.
 Due to the solvents present, it is recommended that polyvinyl alcohol or nitrile rubber gloves be worn.

Eye and face protection:

Avoid contact with the skin and eyes. Wear safety goggles
 Provide eye washes in workshops where the product is constantly handled

Skin protection:

For further information, see § 11 of S.D.S. - Toxicological information.

9 - PHYSICAL AND CHEMICAL PROPERTIES

General information:

Physical state: viscous liquid

Important health, safety and environmental information:

pH of the substance or preparation: not relevant.

The pH is impossible to measure or its value is not relevant.

Boiling point/boiling range: 154 °C.

Flash point interval: 23°C. < Flash point: <= 55°C.

vapour pressure: Below 110 kPa (1.10 bar).

Density: > 1

water solubility: Insoluble.

Other information:

melting point/melting range: not specified.

Self-ignition temperature: not specified.



Decomposition point/decomposition range : not specified.

10 - STABILITY AND REACTIVITY

When exposed to high temperatures, the preparation may release dangerous decomposition products such as carbon monoxide and dioxide, smoke and nitrogen oxide

In contact with water or moist air, the preparation releases dangerous quantities of highly flammable gases at a minimum rate of 1 litre/kg/h

11 - TOXICOLOGICAL INFORMATION

No data is available regarding the preparation itself.

Exposure to vapors from solvents contained in the preparation beyond the exposure limits stated may produce effects harmful to health, such as: Irritation of mucous membrane and respiratory system, kidneys, liver and central nervous system.

Symptoms produced will include headaches, numbness, dizziness, fatigue, muscular asthenia and, in extreme cases, loss of consciousness.

Prolonged or repeated contact with the preparation may strip the skin of its natural oil and thus cause non-allergic dermatitis on contact and absorption through the epidermis.

Splashes in the eyes may cause irritation and reversible damage

It is generally agreed that substances contained are likely to cause significant irritation which lasts for at least twenty four hours after application to the healthy, unbroken skin of an animal for a period of up to 4 hours.

12 - ECOLOGICAL INFORMATION

No ecological data on the product itself is available.

The product must not be allowed to run into drains or waterways.

Ecotoxicity:

Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

13 - DISPOSAL CONSIDERATIONS

Do not pour into drains or waterways.

Waste:

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Soiled packaging:

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

14 - TRANSPORT INFORMATION

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2005 - IMDG 2004 - ICAO/IATA 2005).

UN1263=PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning and reducing compound)

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.
	3	F1	III	3	30	LQ7	163-650-640E



IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.
	3	-	III	5 L	F-E,S-E	163 223 944 955

Not subject to this regulation if Q < 30l
Marine Pollutant P



IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note



3	-	III	309	60 L	310	220 L	A3 A72
3	-	III	Y309	10 L	-	-	-

15 - STATUTORY INFORMATION

This preparation was classified in compliance with the directive known as <All preparations> 1999/45/EC and its adaptations In addition directive 2004/73/EC with the 29° adaptation of directive 67/548/EEC (Hazardous substances) have been taken into account.

Preparation classification:

Harmful. Dangerous for the environment. Flammable.



Contains:

601-022-00-9
601-043-00-3

O-XYLENE
1,2,4-TRIMETHYLBENZENE

Particular hazards associated with the preparation and safety recommendations:

- R 50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- R 38 Irritating to skin.
- R 20/21 Harmful by inhalation and in contact with skin.
- R 15 Contact with water liberates extremely flammable gases.
- R 10 Flammable.
- S 2 Keep out of reach of children.
- S 29 Do not empty into drains.
- S 36/37 Wear suitable protective clothing and gloves.
- S 43 In case of fire, use ... (indicate in the space the precise type of fire-fighting equipment. If water increases risk, add - ' never use water').
- S 46 If swallowed, seek medical advice immediately and show this container or label.
- S 61 Avoid release to the environment. Refer to special instructions/Safety data sheets.
- S 13 Keep away from food, drink and animal feedingstuffs.
- S 23 Do not breathe gas/fumes/vapour/spray (appropriate wording to be specified by the manufacturer).
- S 24/25 Avoid contact with skin and eyes.
- S 51 Use only in well ventilated areas.
- S 62 If swallowed, do not induce vomiting : seek medical advice immediately and show this container or label.
- S 64 If swallowed, rinse mouth with water (only if the person is conscious)
- S 7/9 Keep container tightly closed and in a well- ventilated place.
- S 8 Keep container dry.

- S 1/2 Keep locked up and out of reach of children.
- S 45 In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
- S 53 Avoid exposure - obtain special instructions before use.
- S 2 Keep out of reach of children.

Particular provisions:

Tactile warning of danger.

16 - OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The product must not be used for any purposes other than those specified under heading 1 without first obtaining written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information given on this safety data sheet must be regarded as a description of the safety requirements relating to our product and not a guarantee of its properties

Full text of risk phrases appearing in section 2:

- R 10 Flammable.
- R 20 Harmful by inhalation.
- R 20/21 Harmful by inhalation and in contact with skin.



- | | |
|------------|--|
| R 36/37/38 | Irritating to eyes, respiratory system and skin. |
| R 37 | Irritating to respiratory system. |
| R 38 | Irritating to skin. |
| R 50/53 | Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. |
| R 51/53 | Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. |
| R 65 | Harmful. may cause lung damage if swallowed. |