



1 - IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Identification of the substance or preparation:

Name: **POLYTOP PU 99 BASE.**

Product code: H 1858 B.

Company/undertaking identification:

Registered company name: MAP YACHTING.

Address : ZI ATHELIA IV – 296 Av de la Tramontane – 13705 LA CIOTAT - France.

Telephone : 33 (0)4 42 98 14 50 Fax :33 (0)4 42 98 14 51. Email : sales@map-yachting.com

Emergency telephone: 01 45 42 59 59.

Association/Organisation: ORFILA.

Use of the substance/preparation:

2 - COMPOSITION/INFORMATION ON INGREDIENTS

Full text of risk phrases appearing in section 2: see section 16.

Hazardous substances present on their own:

(present in the preparation at a sufficient concentration to give it the toxicological characteristics it would have in a 100% pure state)

This preparation contains no hazardous substance in this category.

Other substances representing a hazard:

INDEX	CAS	EC	Name	Symb.	R:	%
601-024-00-X	103-65-1	203-132-9	PROPYLBENZENE	Xn N	10 37 51/53 65	0 <= x % < 2.5
601-025-00-5	108-67-8	203-604-4	MESITYLENE	Xi N	10 37 51/53	0 <= x % < 2.5
601-043-00-3	95-63-6	202-436-9	1,2,4-TRIMETHYLBENZENE	Xn N	10 36/37/38 51/53 20	2.5 <= x % < 10
607-025-00-1	123-86-4	204-658-1	N-BUTYL ACETATE		10 66 67	10 <= x % < 25

Substances present at a concentration below the minimum danger threshold:

INDEX	CAS	EC	Name	Symb.	R:	%
607-195-00-7	108-65-6	203-603-9	2-METHOXY-1-METHYLETHYL ACETATE	Xi	10 36	0 <= x % < 2.5
M 00129	64742-95-6	265-199-0	SOLVANT NAPhte AROMATIQUE LEGER (PETROLE)	Xn	65 66 67	2.5 <= x % < 10

Other substances with occupational exposure limits:

No known substance in this category present.

Other components:

3 - IDENTIFICATION OF HAZARDS

This product is classed: Flammable.

Repeated exposure may cause skin dryness or cracking.

Vapors may cause drowsiness and dizziness.

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Other data:

4 - FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing in an unconscious person.

In the event of exposure by inhalation:

If a large quantity is inhaled, move the patient into the fresh air and keep him/her warm and still.

In the event of splashes or contact with eyes:

Wash thoroughly with soft, clean water for 15 minutes holding the eyelids open.



Refer the patient to an ophthalmologist, in particular if there is any redness, pain or visual impairment.

In the event of splashes or contact with skin:

Remove contaminated clothing and wash the skin thoroughly with soap and water or a recognised cleaner.
DO NOT use solvents or thinners.

In the event of swallowing:

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.
If swallowed accidentally, call a doctor to assess the need for monitoring and subsequent treatment in hospital. Show him the label.

Specific and immediate treatment:

Information for the doctor:

5 - FIRE-FIGHTING MEASURES

Chemical powders, carbon dioxide and other extinguishing gas are suitable for small fires.

Suitable extinguishing media:

Carbon dioxide, chemical powders, foams, and other extinguishing gases.
In the event of fire, use specifically suitable extinguishing agents. Never use water.

Extinguishing media which must not be used for safety reasons:

Water is not generally recommended since it can be ineffective; however, it can be used successfully to cool containers exposed to the fire and to disperse fumes.
A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.
Do not breathe in smoke.
Prevent the effluent of fire-fighting measures from entering drains or waterways.

Special protective equipment for fire-fighters:

Fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.

Special exposure hazards arising from the substance or preparation itself, combustion products, resulting gases:

6 - ACCIDENTAL RELEASE MEASURES

Personal precautions:

On account of the organic solvents contained in the preparation, eliminate sources of ignition and ventilate the premises.
Avoid inhaling the vapors.
Consult the safety measures listed under headings 7 and 8.

Environmental precautions:

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.
Prevent any material from entering drains or waterways.
Use drums to dispose of waste recovered in accordance with applicable regulations (see heading 13).
If the product contaminates waterways, rivers or drains, alert the relevant authorities in accordance with statutory procedures

Methods for cleaning up:

Clean preferably with a detergent, do not use solvents.

7 - HANDLING AND STORAGE

The regulations relating to storage premises apply to workshops where the product is handled.

Handling:

Handle in well-ventilated areas.
The vapors are denser than air. They can spread along the ground and form explosive mixtures with air
Prevent the formation of flammable or explosive concentrations in air and avoid vapor concentrations higher than the occupational exposure limits.

Fire prevention:

Prevent the accumulation of electrostatic charges with connections to earth
The preparation may become electrostatically charged; always place on the ground during transfer. Wear antistatic shoes and clothes and make floors of conductive materials.



Use the product in premises where there are no naked flames or other sources of ignition and have protected electrical equipment
 Keep packages tightly closed and away from sources of heat, sparks and naked flames.
 Do not use tools which may produce sparks. Do not smoke.
 Prevent access by unauthorised personnel.

Recommended equipment and procedures:

For personal safety, see §8.
 Observe precautions stated on label and also industrial safety regulations
 Avoid inhaling solvent vapors and spray-gun aerosols
 Packages which have been opened must be reclosed carefully and stored in an upright position
 Avoid inhaling vapors.
 Where the personnel must carry out work in a booth, whether for spraying or otherwise, the ventilation may be inadequate to control particles and solvent vapors in every case.
 It is therefore recommended that personnel wear masks with a compressed air supply during spraying operations until the concentration of particles and solvent vapors has fallen below the exposure limits.

Prohibited equipment and procedures:

Smoking, eating and drinking are prohibited in premises where the preparation is used
 Never open the packages under pressure

Storage:

Keep the container tightly closed in a dry place.
 Keep away from all sources of ignition - do not smoke.
 Keep well away from all sources of ignition, heat and direct sunlight
 The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area.

Specific use(s):

8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

Use personal protection equipment as per Directive 89/686/EEC.

Technical measures:

Ensure adequate ventilation, if possible with extractor fans at work posts and appropriate general extraction.
 If this ventilation is insufficient to maintain the concentration of solvent vapors below the exposure limits, wear breathing apparatus

Exposure limit values per INRS ND 2098-174-99 and ND 2114-176-99:

France	VME-ppm:	VME-mg/m3:	VLE-ppm:	VLE-mg/m3:	Notes:	TMP N°:
108-65-6	50	275	100	550	*	--
123-86-4	150	710	200	940	-	84
95-63-6	20	100	-	-	-	84 -
108-67-8	20	100	-	-	-	84 -

Exposure limit values per 2000/39/EC and 98/24/EC:

EC	VME-ppm:	VME-mg/m3:	VLE-ppm:	VLE-mg/m3:	Notes:
108-65-6	50	275	100	550	Peau
95-63-6	20	100	-	-	-
108-67-8	20	100	-	-	-

Exposure limit values (2003):

UK/OES	TWA:	STEL:	Ceiling:	Definition:	Criterion:
108-65-6	50 ppm	100 ppm	-	-	-
123-86-4	150 ppm	200 ppm	-	-	-
95-63-6	25 ppm	-	-	-	-
108-67-8	25 ppm	-	-	-	-
ACGIH/TLV	TWA:	STEL:	Ceiling:	Definition:	Criterion:
123-86-4	150 ppm	200 ppm	-	-	-
95-63-6	25 ppm	-	-	-	-



108-67-8	25 ppm	-	-	-	-
Germany/MAK	TWA:	STEL:	Ceiling:	Definition:	Criterion:
108-65-6	50 ppm	50 ppm	-	-	-
123-86-4	100 ppm	200 ppm	-	-	-
95-63-6	20 ppm	40 ppm	-	-	-
108-67-8	20 ppm	40 ppm	-	-	-

Respiratory protection:

Where workers encounter concentrations higher than the exposure limits, they must wear suitable, approved masks.

Hand protection:

Protective creams may be used for exposed skin, but they should not be applied after contact with the product.

Due to the solvents present, it is recommended that polyvinyl alcohol or nitrile rubber gloves be worn.

Eye and face protection:

Use eye protectors designed to protect against liquid splashes

Skin protection:

For further information, see § 11 of S.D.S. - Toxicological information.

Environmental exposure controls:

9 - PHYSICAL AND CHEMICAL PROPERTIES

General information:

Physical state: viscous liquid

Important health, safety and environmental information:

pH of the substance or preparation: not relevant.

The pH is impossible to measure or its value is not relevant.

Boiling point/boiling range: not specified.

Flash point interval: 23°C. < Flash point: <= 55°C.

vapour pressure: Below 110 kPa (1.10 bar).

Density: > 1

water solubility: Insoluble.

Other information:

melting point/melting range: not specified.

Self-ignition temperature: not specified.

Decomposition point/decomposition range : not specified.

10 - STABILITY AND REACTIVITY

When exposed to high temperatures, the preparation may release dangerous decomposition products such as carbon monoxide and dioxide, smoke and nitrogen oxide

Conditions to avoid:
Materials to avoid:
Hazardous decomposition products:

11 - TOXICOLOGICAL INFORMATION

No data is available regarding the preparation itself.

Exposure to vapors from solvents contained in the preparation beyond the exposure limits stated may produce effects harmful to health, such as:

Irritation of mucous membrane and respiratory system, kidneys, liver and central nervous system.

Symptoms produced will include headaches, numbness, dizziness, fatigue, muscular asthenia and, in extreme cases, loss of consciousness.

Prolonged or repeated contact with the preparation may strip the skin of its natural oil and thus cause non-allergic dermatitis on contact and absorption through the epidermis.

Splashes in the eyes may cause irritation and reversible damage

In the event of exposure by inhalation:



In the event of swallowing:

In the event of splashes or contact with skin:

In the event of splashes or contact with eyes:

Other data:

12 - ECOLOGICAL INFORMATION

No ecological data on the product itself is available.

The product must not be allowed to run into drains or waterways.

Mobility:

Persistence and degradability:

Bioaccumulative potential:

Ecotoxicity:

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Other adverse effects:

13 - DISPOSAL CONSIDERATIONS

Do not pour into drains or waterways.

Waste:

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Soiled packaging:

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

Local arrangements:

Codes of wastes (Decision 2001/573/EC, Directive 75/442/EEC, Directive 91/689/EEC on hazardous waste) :

14 - TRANSPORT INFORMATION

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2005 - IMDG 2004 - ICAO/IATA 2005).

UN1263=PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning and reducing compound)

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	
	3	F1	III	3	30	LQ7	163-650-640E	
Not subject to this regulation if Q < 450l.								
IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.		
	3	-	III	5 L	F-E,S-E	163 223 944 955		
Not subject to this regulation if Q < 30l								
IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note
	3	-	III	309	60 L	310	220 L	A3 A72
	3	-	III	Y309	10 L	-	-	-

15 - STATUTORY INFORMATION

This preparation was classified in compliance with the directive known as <All preparations> 1999/45/EC and its adaptations

In addition directive 2004/73/EC with the 29° adaptation of directive 67/548/EEC (Hazardous substances) have been taken into account.

Preparation classification:

Flammable.

Contains:

Particular hazards associated with the preparation and safety recommendations:



- | | |
|---------|---|
| R 52/53 | Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. |
| R 10 | Flammable. |
| R 66 | Repeated exposure may cause skin dryness or cracking. |
| R 67 | Vapours may cause drowsiness and dizziness. |

Particular provisions:

16 - OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The product must not be used for any purposes other than those specified under heading 1 without first obtaining written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information given on this safety data sheet must be regarded as a description of the safety requirements relating to our product and not a guarantee of its properties

Full text of risk phrases appearing in section 2:

- | | |
|------------|---|
| R 10 | Flammable. |
| R 20 | Harmful by inhalation. |
| R 36 | Irritating to eyes. |
| R 36/37/38 | Irritating to eyes, respiratory system and skin. |
| R 37 | Irritating to respiratory system. |
| R 51/53 | Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. |
| R 65 | Harmful. may cause lung damage if swallowed. |
| R 66 | Repeated exposure may cause skin dryness or cracking. |
| R 67 | Vapours may cause drowsiness and dizziness. |