



Written by -  
Jean-Pierre GROS  
Technical Manager

Checked by - A.DURRIEU :

SDS : RA023B/A  
Edition : 1<sup>st</sup> of January 1999  
Revision :  
Page : 1/3

Quality assurance

## SAFETY DATA SHEET AEROPRIM EPU 523 Base

### 1 - IDENTIFICATION OF PREPARATION AND COMPANY/BUSINESS

#### Preparation:

Name: **AEROPRIM EPU 523 BASE**

#### Company/business:

Registered company name: SICOMIN

Address: BP23 – RN 568-13161 CHATEAUNEUF LES MARTIGUES Cedex

E.mail: [Composites@sicomin.com](mailto:Composites@sicomin.com)

Telephone 33 (0)4 42 42 30 20 Fax: 33 (0)4 42 81 29 29

Emergency telephone No.: 01 45 42 59 59 . Association/Organisation: ORFILA.

### 2 - INFORMATION REGARDING CONSTITUENTS

Hazardous substances present on their own.

(present in the preparation at a sufficient concentration to give it the toxicological characteristics it would have in a 100% pure state)

024-009-00-4 STRONTIUM CHROMATE Concentration  $\geq$ 10.00% and  $<$ 25.00%. Symbol: T N R: 45.C2-50/53-22

Other substances representing a hazard:

601-022-00-9 XYLENE Concentration  $\geq$ 2.50% and  $<$ 10.00%. Symbol: Xn R: 10-38-902-20/21

601-023-00-4 ETHYLBENZENE Concentration  $\geq$ 0.00% and  $<$ 2.50%. Symbol: Xn F R: 11-20-902

606-002-00-3 METHYL ETHYL KETONE Concentration  $\geq$ 10.00% and  $<$ 25.00%. Symbol: Xi F R: 11-36/37

606-010-00-7 CYCLOHEXANONE Concentration  $\geq$ 2.50% and  $<$ 10.00%. Symbol: Xn R: 10-20

607-195-00-7 2-METHOXY-1-METHYLETHYL ACETATE Concentration  $\geq$ 10.00% and  $<$ 25.00%. Symbol: Xi R: 10-36

Substances present at a concentration below the minimum danger threshold.

No known substance in this category present.

Other substances with occupational exposure limits.

606-004-00-4 METHYL ISOBUTYL KETONE Concentration  $\geq$ 2.50% and  $<$ 10.00%. Symbol: F R: 11

### 3 - IDENTIFICATION OF HAZARDS

This product is classed: Highly flammable liquid.

Possibility of irritation to the eyes and by inhalation.

Possibility of category two carcinogenic effects.

Possibility of acute, lethal, noxious effects with symptoms of slight poisoning by inhalation, contact with the skin and swallowing.

### 4 - FIRST AID.

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing in an unconscious person.

In the event of exposure by inhalation.

In the event of inhalation, move the patient into the fresh air and keep him/her warm and still.

If breathing is irregular or has stopped, effect mouth-to-mouth resuscitation and call a doctor.

Do not give the patient anything orally.

If the person is unconscious, place in the recovery position and call an ambulance.

In the event of splashes or contact with eyes.

Wash thoroughly with soft, clean water for 15 minutes holding the eyelids open.

Refer the patient to an ophthalmologist, in particular if there is any redness, pain or visual impairment.

In the event of splashes or contact with skin.

Remove contaminated clothing and wash the skin thoroughly with soap and water or a recognised cleaner.

DO NOT use solvents or thinners.

If the contaminated area is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital

In the event of swallowing.

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water, administer activated medical charcoal and consult a doctor.

Keep still. DO NOT induce vomiting.

Consult a doctor and show him the label.

Call a doctor immediately and show him the label.

### 5 - FIRE-FIGHTING MEASURES

Chemical powders, carbon dioxide and other extinguishing gas are suitable for small fires.

In the event of fire, the recommended extinguishing agents are:

Special foams for polar liquids (known as alcohol resistant), powders, carbon dioxide.

In the event of fire, use specifically suitable extinguishing agents. Never use water.

Extinguishing agents not to be used

Water is not generally recommended since it can be ineffective; however, it can be used successfully to cool containers exposed to the fire and to disperse fumes.

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

Prevent the effluent of fire-fighting measures from entering drains or waterways.

Special equipment for fire-fighting personnel.

Fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.

### 6 - MEASURES TO BE TAKEN IN THE EVENT OF ACCIDENTAL SPILLAGE

Safety precautions:

Eliminate any possible source of ignition and ventilate the premises.

Avoid inhaling the fumes.

Avoid any contact with the skin and eyes.

Consult the safety measures listed under headings 7 and 8.

If a large quantity has been spilt, evacuate all personnel and only allow intervention by trained operators equipped with safety apparatus.

Environmental safety precautions:

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatom earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

Use drums to dispose of waste recovered in accordance with applicable regulations (see heading 13).

If the product contaminates waterways, rivers or drains, alert the relevant authorities in accordance with statutory procedures

Cleaning methods:

Clean preferably with a detergent, do not use solvents.

### 7 - HANDLING AND STORAGE

The regulations relating to storage premises apply to workshops where the product is handled.

Handling:

Handle in well-ventilated areas.

The fumes are denser than air. They can spread along the ground and form explosive mixtures with air

Prevent the formation of flammable or explosive concentrations in air and avoid vapour concentrations higher than the occupational exposure limits.



Written by -  
Jean-Pierre GROS  
Technical Manager

Checked by - A.DURRIEU :

SDS : RA023B/A  
Edition : 1<sup>st</sup> of January 1999  
Revision :  
Page : 2/3

Quality assurance

Fire prevention:  
Prevent the accumulation of electrostatic charges with connections to earth  
The preparation may become electrostatically charged; always place on the ground during transfer. Wear antistatic shoes and clothes and make floors of conductive materials.  
Use the product in premises where there are no naked flames or other sources of ignition and have protected electrical equipment  
Keep packages tightly closed and away from sources of heat, sparks and naked flames.  
Do not use tools which may produce sparks. Do not smoke.  
Prevent access by unauthorised personnel.  
Recommended equipment and procedures  
Observe precautions stated on label and also industrial safety regulations  
Packages which have been opened must be reclosed carefully and stored in an upright position  
Avoid inhaling fumes. Carry out any industrial operation which may give rise to this in a sealed apparatus.  
In all cases, recover emissions at source  
Provide fume extraction at the emission source and also general ventilation of the premises  
Also provide breathing apparatus for certain short tasks of an exceptional nature and for emergency interventions  
Where the personnel must carry out work in a booth, whether for spraying or otherwise, the ventilation may be inadequate to control particles and solvent fumes in every case.  
It is therefore recommended that personnel wear masks with a compressed air supply during spraying operations until the concentration of particles and solvent fumes has fallen below the exposure limits.  
Avoid inhaling dust and spray-gun aerosol particles produced by application of this preparation  
In the case of paints, also avoid inhaling dust, particles and fumes during treatment of surfaces coated with this preparation by dry sand blasting or by heating operations (welding, soldering, cutting etc.)  
Do not breathe in aerosols.  
Avoid contact of product with the skin and eyes  
Prohibited equipment and procedures.  
Smoking, eating and drinking are prohibited in premises where the preparation is used  
Never open the packages under pressure  
Storage.  
Keep the container tightly closed in a dry, well-ventilated place  
Keep away from food and drink, including those for animals.  
Keep away from all sources of ignition - do not smoke.  
Keep well away from all sources of ignition, heat and direct sunlight  
The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area.

**8 - EXPOSURE CONTROL - PERSONAL SAFETY**

Technical measures.  
Ensure adequate ventilation, if possible with extractor fans at work posts and appropriate general extraction.  
Check the atmosphere periodically.  
If this ventilation is insufficient to maintain the concentration of fumes below the exposure limits, wear breathing apparatus  
Exposure limits per INRS ND 1945-153-93/(1996) and ND 2022-163-96:

France	VME-ppm:	VME-mg/m3:	VLE-ppm:	VLE-mg/m3:	Notes:	TMP N°:
024-009-00-4	-	-	-	-	-	-
601-022-00-9	100	435	150	650	-	4bis, 84
601-023-00-4	100	435	-	-	-	84
606-002-00-3	200	600	-	-	-	84
606-004-00-4	50	205	-	-	-	84
606-010-00-7	25	100	-	-	-	84

607-195-00-7	-	-	-	-	-	-
Germany	Class:	MAK-ppm:	MAK-mg/m3:	Notes:	Notes:	
024-009-00-4	-	-	-	-	-	
601-022-00-9	II,1	100	440	-	-	
601-023-00-4	-	100	440	*	-	
606-002-00-3	II,1	200	590	-	-	
606-004-00-4	II,2	100	400	-	-	
606-010-00-7	-	-	-	B*	-	
607-195-00-7	I	50	275	-	-	
ACGIH(TLV)	TWA-ppm:	TWA-mg/m3:	STEL-ppm:	STEL-mg/m3:	Notes:	Notes:
024-009-00-4	-	0,0005	-	-	A2	
601-022-00-9	100	434	150	651	-	
601-023-00-4	100	434	125	543	-	
606-002-00-3	200	590	300	885	-	
606-004-00-4	50	205	75	307	-	
606-010-00-7	25	100	-	-	*	
607-195-00-7	-	-	-	-	-	

Safety breathing apparatus:  
With this preparation, avoid in particular any inhalation of fumes.  
Hand protection.  
Protective creams may be used for exposed skin, but they should not be applied after contact with the product.  
Due to the solvents present, it is recommended that polyvinyl alcohol or latex rubber gloves be worn  
Eye and face protection.  
Avoid contact with eyes.  
Wear safety goggles.  
Provide eye washes in workshops where the product is constantly handled  
Skin protection.

For further information, see § 11 of S.D.S. - Toxicological information.

**9 - PHYSICAL PROPERTIES**

Density: > 1  
Acid/base character of preparation: neutral.  
Solubility of preparation in water: Insoluble.  
Vapour tension at 50°C of volatile constituents: Below 110Kpa (1.10 bar).  
Physical state: viscous liquid  
Flash point interval: Flash point: <= 21°C.  
When a pH measure is possible, it has a value of: not stated.  
Self-ignition temperature: 450 °C.  
Decomposition temperature: not relevant.  
Melting temperature interval: -80 °C.  
Average distillation temperature of solvents contained: 116 °C.

**10 - STABILITY AND REACTIVITY**

When exposed to high temperatures, the preparation may release dangerous decomposition products such as carbon monoxide and dioxide, smoke and nitrogen oxide  
Any apparatus likely to produce a flame or to have a metallic surface at high temperature (burners, electric arcs, furnaces etc.) must not be allowed on the premises.

**11 - TOXICOLOGICAL INFORMATION**

No data is available regarding the preparation itself.  
Exposure to fumes from solvents contained in the preparation beyond the exposure limits stated may produce effects harmful to health, such as:  
Irritation of mucous membrane and respiratory system, kidneys, liver and central nervous system.



Written by -  
Jean-Pierre GROS  
Technical Manager

Checked by - A.DURRIEU :

SDS : RA023B/A  
Edition : 1<sup>st</sup> of January 1999  
Revision :  
Page : 3/3

Quality assurance

Symptoms produced will include headaches, numbness, dizziness, fatigue, muscular asthenia and, in extreme cases, loss of consciousness.  
Prolonged or repeated contact with the preparation may strip the skin of its natural oil and thus cause non-allergic dermatitis on contact and absorption through the epidermis.  
Splashes in the eyes may cause irritation and reversible damage  
It is generally agreed that substances contained are likely to cause serious irritation of the respiratory system and, when applied to the eye of an animal, the appearance of major lesions which persist for at least twenty-four hours.  
It is generally agreed that substances contained are likely to cause category 2 carcinogenic effects.

**12 - ECOLOGICAL INFORMATION**

No ecological data on the product itself is available.  
The product must not be allowed to run into drains or waterways.

**13 - DISPOSAL CONSIDERATIONS**

Do not pour into drains or waterways.

**14 - TRANSPORT INFORMATION**

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport  
UN 1263 = Paint flammable (including lacquer, enamel, stain, shellac, varnish, polish and related material).

ADR/RID	Class	Number	Code	Identif.	Label
	3	5° c)	33	1263	3

  

IMDG	Page	N°ONU	Class	Number	2°Label	Identif.	N°GSMU
		1263	3.3	III	-	3-05	310

The page number 3372 should not appear anymore on the Dangerous Goods Declaration (Amendment 28-96).

IATA	N°ONU	Class	2°Label	Number	Passenger	Passenger	Freighter
	Freighter nota						
	1263	3	-	III	309	60 L	310 220

  

L	A72	Class	2°Label	Number	Passenger	Passenger	Freighter
	1263	3	-	III	Y309	10 L	- -

**15 - STATUTORY INFORMATION**

This preparation was classified in compliance with the directive known as <All preparations> 88/379/EEC and its adaptations

In addition directive 96/54/EC with the 22° adaptation of directive 67/548/EEC (Hazardous substances) have been taken into account.

Preparation classification.

Toxic. Highly flammable.

Contains:

024-009-00-4 STRONTIUM CHROMATE

601-022-00-9 XYLENE

601-023-00-4 ETHYLBENZENE

606-010-00-7 CYCLOHEXANONE

Particular hazards associated with the preparation and safety recommendations:

- R 36/37 Irritating to eyes and respiratory system.
- R 20/21/22 Harmful by inhalation, in contact with skin and if swallowed.
- R 11 Highly flammable.
- R 45 May cause cancer.
- For professional use only.
- S 26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- S 53 Avoid exposure - obtain special instructions before use.
- S 36/37 Wear suitable protective clothing and gloves.

- S 23 Do not breathe vapour.
- S 33 Take precautionary measures against static discharges.
- S 16 Keep away from sources of ignition - no smoking.
- S 38 In case of insufficient ventilation, wear suitable respiratory equipment.
- S 9 Keep container in a well-ventilated place.
- Product not to be sold to the general public.

Particular provisions:  
Product not to be sold to the general public. (Dir 94/60/EEC) - For professional use only.  
Attention - Avoid exposure - obtain special instructions before use.

**16 - OTHER INFORMATION**

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.  
The product must not be used for any purposes other than those specified under heading 1 without first obtaining written handling instructions.  
It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.  
The information given on this safety data sheet must be regarded as a description of the safety requirements relating to our product and not a guarantee of its properties