

**1- Product and company identification**

Trade name: **DM 06**  
**Curing agent for epoxy resin**

**Manufacturer / Supplier:**

**SICOMIN Composites** RN 568 Quartier la Moutte BP 23  
13 161 Châteauneuf-les-Martigues Cédex -France-  
Tél: 33.04.42.42.30.20 Fax: 33.04.42.81.29.29 composites@sicomin.com

**2- Composition / Information on ingredients**

**Chemical characterization:** Polyamines and base Mannich

<b>Chemical Name</b>	<b>Cas number</b>	<b>%</b>	<b>Symbol</b>	<b>Risk Classification</b>
m-Xylene diamin XDA	1477-55-0	< 40	C	20/22 34 43
Bisphenol A	80-05-7	< 40	Xi	36/37/38 43

**3- Hazards Identification**

C: Corrosive

R 21/22 Harmful by skin contact and if swallowed

R 34: Causes burns

R 43: May cause sensitization by skin contact

**Signs and symptoms of exposure (Possible longer term effects):**

Repeated and/or prolonged exposures may result in : adverse respiratory effects (such as cough, tightness of chest or shortness of breath); adverse skin effects (such as defatting, rash, irritation or corrosion); adverse eye effects (such as conjunctivitis or corneal damage).

**4- First aid measures**

Signs and symptoms of exposure (acute effects)

Eye contact:

Rinse immediately with plenty of water for at least 15'. Get medical attention.

Skin contact:

Immediately remove contaminated clothing. Remove the excess and wash with water and soap.  
Get medical attention.

Ingestion:

Do not induce vomiting. Consult immediately a physician

Inhalation:

Remove from the contaminated area and keep warm and at rest.

**5- Fire fighting measures**

Suitable extinguishing agents:

Powder CO<sub>2</sub>, foam. Cool the containers with water spray

Products to avoid:

ND

Products of combustion will include:

Poison gas as nitrogen gas (NOx), ammoniac, carbon monoxide (CO)

Protective equipment:

Use breathing apparatus

## 6- Accidental release measures

### Individual precautions:

- Use gloves, goggles, masks and protective clothing
- Use breathing equipment if the area is narrow, keep fire sources away

### Environmental precautions:

- Keep the product away from superficial and underground water. In the event of product entering waters or drainage system or pollution soil or plants, informing fire service or police.

### Cleaning procedures:

- Soak up inert material in accordance with law regulations. Wash with water & detergents.

## 7- Handling and storing

### Handling:

- Use personal protection (see point 8). Provide adequate ventilation. Avoid inhalation vapours.

### Storing:

- Store in well ventilated area, in close containers.
- The product is sensitive to CO<sub>2</sub> and humidity.

## 8- Exposure controls / personal protection

### Precautionary measures:

- Provide adequate ventilation
- CAS 1477-55-0: VME 0.1 mg/m<sup>3</sup>

### Respiratory protection:

- Necessary in case the area is not well ventilated: mask with adequate filters

### Hand protection:

- Use appropriate gloves

### Eyes protection:

- Wear goggles or a face visor

### Skin protection:

- Use protective clothing, exercising reasonable personal cleanliness

## 9- Chemical / Physical properties

Appearance	: Liquid	
Colour	: Yellow	
Odour	: Amoniacal	
Ph	: 11, Alcaline	ISO 8975
Boiling point	: > 200 °C	DIN 53171
Flash point	: > 100°C	DIN 51758
Solubility in water	: Partially soluble	
Solubility in organic solvents	: Alcohols and aromatic hydrocarbons	
Specific gravity (Kg / l 20°C)	: 1.02 ± 0.02	ISO 2811
Viscosity (mPa.s 25°C)	: 1100 ±100	ISO 9371
Pression de vapeur (mm Hg à 25°C)	: < 0.1 mbar	

## 10- Stability and reactivity data

### Precautions: ND

### Materials to avoid:

- Acids, strong oxidizers, epoxidies, ketones

### Hazardous decomposition products:

- In case of fire, the product may develop toxic gas as nitrous gas (NO<sub>x</sub>), carbon monoxide (CO), NH<sub>x</sub>, etc..

### 11- Toxicological information

Consider the concentration of each substance to evaluate toxicological effects caused by exposure

Cas number	Inhalation LD 50 (rat) mg / l / 4h	Ingestion LD 50 (rat) mg/kg	Skin contact LD 50 (rabbit) mg/kg	Long term effect Skin cobaye
1477-55-0	2.4	1040	nd	nd
80-05-7	nd	3300	3000	no irritating

Ingestion:

Corrosive. May cause burns of mouth and severe gastrointestinal trouble.

Skin absorption:

Prolonged or widespread exposure may result in the absorption of potentially harmful amounts of material.

May cause chemical burns and develop skin allergy.

Inhalation:

Vapours are irritating and may develop allergy.

Eye contact:

May cause severe irritation with corneal injury which may result in permanent impairment of vision, even blindness.

### 12- Ecological Information

General notes:

Do not empty into drains

### 13- Disposal considerations

Dispose of in accordance with local and national regulations

### 14- Transport Information

Correct technical name: Amines, liquid, corrosives, nos

Content: m-Xylenediamin, Bisphenol A

ONU N°: 2735

Air transport - OACI / IATA Class 8 Group: II

Sea transport - IMDG Class 8 Group: II IMDG page: 8109.2  
N° EMS: 8-05 MFAG: 320 Marine pollutant: no

Road transport - ADR / RID Class 8, 53(b) HI/Kemler n°: 80 label: 8

### 15- Regulatory information

Label EEC:

Regulation 88 / 379

Hazard symbol:

C Corrosive

Risk Phrases :

R 21/22 Harmful by skin contact and if swallowed

R 34: Causes burns

R 43: May cause sensitization by skin contact

**Safety Phrases:**

- S 26: In case of contact with eye, rinse immediatly with plenty of water and seek medical advice
- S 36/37/39: Wear suitable protective clothing, gloves, and eye face protection
- S 38: In case the area is not well ventilated: mask with adequate filters
- S 46 In case of accident or if you feel unwell, seek medical advice
- S 61 Avoid release to the environment. Refer to special instructions / safety data sheets

**16-Other information**

Note:

The information herein is given in good faith and to the best of our knowledge but no warranty, express or implied, is made. Since the use of this information and the conditions of use of the product are not within our control, it is the user's obligation to determine the condition of safe use of the products.

NA: Not applicable      ND: Not determined

**Department issuing data specification sheet / Contact:**

Tel: 33.04.42.42.30.20    Fax: 33.04.42.81.29.29    jean.pierre.gros@sicomin.com