

1- Product and company identificationTrade name: **SR 1500 i
Autoextinguible Epoxy Resin****Manufacturer / Supplier:****SICOMIN Composites
RN 568 BP 23
13 161 Châteauneuf-les-Martigues Cedex - France
Tel: 33.04.42.42.30.20 Fax: 33.04.42.81.29.29****2- Composition / Information on ingredients****Chemical characterization:** Modified epoxy resin

CAS Number	Chemical Name:	%	Symbol	R Classification
25068-38-6	Bisphenol A Diglycidyléther (DGEBA)	< 80	Xi, N	36/38 43 51/53
028064-14-4	Epoxide derivatives mw < 700	< 40	Xi, N	36/38 43 51/53
2461-15-62	Ethylhexyl glycidyl éther (EHGE)	< 10	Xi	43
1309-64-4	Antimony trioxyde	< 15	Xn	40 (Powder)

3- Hazards Identification**Hazard designation:**

Xi: Irritant



N: Environmentally hazardous substance

- R 36/38 Irritating to eyes and skin
R 43: May cause sensitization by skin contact
R 51/53: Harmful to aquatic organism, may cause long term adverse effects in aquatic environment

Additional information:

The residue of epichlorohydrin corresponds to the recommendations of APME: modified epoxy resins < 10 ppm (0.001 %)

4- First aid measures**After inhalation:**

Supply fresh air and call for doctor for safety reasons. In case of unconsciousness bring patient into stable side position for transport.

After skin contact:

Instantly wash with water and soap and rinse thoroughly

After eye contact:

Rinse opened eye for several minutes under running water. Seek immediate medical advice

After swallowing:

In case of persistent symptoms consult doctor.

5- Fire fighting measures

Don't burn

Suitable extinguishing agents:

na

Products to avoid:

Water with a full water jet

Special hazards caused by the material, its products of combustion or resulting gases:

Carbon monoxide (CO). Under certain fire conditions, toxic gases cannot be excluded, eg Bromine derivatives

Protective equipment:

Wear full protective suit and self-contained breathing apparatus